AMAZING FUN, EVEN U<u>NDERWATER</u>



COOLPIX W150

Unlock a world of fun and adventure with the COOLPIX W150. From a sunny beach, to a winter wonderland, this camera was built to endure various environments. Enjoy a waterproof depth of down to 10 metres, shock resistance from falls up to 1.8 metres, cold resistance down to -10°C, and a dustproof design. Made with comfort in mind, the exterior consists of ergonomic grips and large, easy-to-use, operational buttons. Shoot and share incredible scenes wherever you go with 13.2 megapixels, 1080p/30 fps Full HD movie recording and SnapBridge 2.5.



READY FOR ANYTHING

Enjoy pixel-perfect performance worry-free with the COOLPIX W150. Whether you're capturing beautiful moments on land, or in the water, get the most out of every moment with this robust and reliable camera. Waterproof to 10m, Shockproof from 1.8m, along with a freezeproof and dustproof construction make the COOLPIX W150 extremely durable.



SNAP AND SHARE AWAY

Shoot and share your images with your friends and family instantly. Featuring SnapBridge 2.5, the COOLPIX W150 automatically transfers images to your mobile device for easy storage and sharing on social media. You can even control your camera remotely for easier group shots. Share the highlights of your holiday in an instant with this durable and easy to use camera.



EASY AND EFFECTIVE

Experience a new kind of functionality with COOLPIX W150. Featuring 3x optical zoom and 6x Dynamic Fine Zoom, reliably capture any subject from any distance. Designed to be incredibly intuitive, With easy-to-understand buttons and user interface — with four flexible buttons that link with the menu screen.



UNLEASH YOUR INNER ARTIST

Have a little more fun with the COOLPIX WI50. Explore your creativity with various features like picture in picture mode, picture play and a number of different effects. Create curved pictures, or add stamps and frames to your shots. Let your artistic side run wild. Enjoy a wide range of image editing functions with this easy-to-use family-friendly camera.



COOLPIX W150 - TECHNICAL SPECIFICATIONS

Туре Compact digital camera 13.2 million (Image processing may reduce the number of effective pixels.) 1/3.1-in. type CMOS Total pixels: approx. 14.17 million Effective pixels Image sensor NIKKOR lens with 3 x optical zoom Lens Focal length 4.1 to 12.3 mm (angle of view equivalent to that of 30 to 90 mm lens in 35mm [135] format) Maximum aperture f/ 3.3 to 5.9

6 elements in 5 groups Construction Digital zoom magnification Up to 4x (angle of view equivalent to that of approx. 360 mm lens in 35mm [135] format)

Vibration reduction Electronic VR (movies) Electronic VR (still images) Motion blur reduction Autofocus system Contrast-detect AF

[W]: Approx. 5 cm (2 in.) to ∞ [T]: Approx. 50 cm (1 ft 8 in.) to ∞ (Distances measured from center of front surface of the protective glass) Center, face detection, target finding AF Focus range

Focus-area selection

Monitor size 6.7 cm (2.7 -in.) diagonal

Monitor resolution Approx. 230 k-dot, TFT LCD with anti-reflection coating and 5-level brightness adjustment

Frame coverage (shooting mode) Approx. 96% horizontal and vertical (compared to actual picture) Frame coverage (playback mode) Approx. 100% horizontal and vertical (compared to actual picture)

Media SD, SDHC, SDXC Internal memory (approx. 21 MB)

DCF and Exif 2.31 compliant File system

Still images: JPEG Voice messages: WAV Movies: MP4 (Video: H.264/MPEG-4 AVC, Audio: AAC stereo) File formats

Still Illingss. III - Volce Illissages. WA Movies. Mar 4 (Video I. 1204 Mir 1204 AV Large (18 M) (4160x3120), Medium (4 M) (2272x1704), Small (2 M) (1600x1200) Large (1080p) (1920x1080), Small (640) (640x480), Small (old-fashioned) (640x480) Still images Movies O sensitivity (Standard output sensitivity) ISO 125 to 1600

Metering method Matrix, center-weighted (digital zoom less than 2x), spot (digital zoom 2x or more) Exposure modes Programmed auto exposure and exposure compensation (-2 EV, -1 EV, 0 EV, +0.7 EV, +1.5 EV,

Shutter type Mechanical and CMOS electronic shutter

1/2000 to 1 s 25 s ([Add light trails] in [Choose a style] is set to [Night sky]) Shutter speed

Туре Electronically-controlled ND filter (–2 AV) selection 2 steps (f/3.3 and f/6.6 [W])

Range

Built-in flash

Range (approx.) (ISO sensitivity: Auto) [W]: 0.3 to 3.1 m (1 ft to 10 ft) [T]: 0.6 to 1.7 m (2 ft to 5 ft 6 in.)

Control TTL auto flash with monitor preflashes

USB connector Micro-USB connector (Do not use any USB cable other than the included UC-E21 USB Cable.), Hi-Speed USB Supports Direct Print (PictBridg

HDMI output connector HDMI micro connector (Type D)

IEEE 802.11b/g (standard wireless LAN protoco Standards

Operating frequency 2412 to 2462 MHz (1 to 11 channels) 12.5 dBm (EIRP) Maximum output power

Authentication Open system, WPA2-PSK Communication protocols Bluetooth Specification Version 4.1

Bluetooth: 2402 to 2480 MHz Bluetooth Low Energy: 2402 to 2480 MHz Operating frequency Maximum output powe Bluetooth: 3.5 dBm (EIRP) Bluetooth Low Energy: 3.5 dBm (EIRP)

JIS/IEC protection class 8 (IPX8) equivalent (under our testing conditions) Capacity to shoot images underwater up to a depth of 10 m (33 ft) c Waterproof

JIS/IEC protection class 6 (IP6X) equivalent (under our testing conditions) Dustproof Cleared our testing conditions{sup(*1)} compliant with MILSTD-810G w/Change 1 Method 516.7-Shock One EN-EL19 Rechargeable Li-ion Battery (included) EH-62G AC Adapter (available separately) Approx. 1 h 40 min (when using EH-73P/EH-73PCH Charging AC Adapter and when no charge remains) Shockproof Power sources

Charging time Battery life of still shooting Approx. 220 shots when using EN-EL19(sup(*2)) Approx. 1 h 35 min when using EN-EL19{sup(*2)}{sup(*3)}

Battery life of movies (actual battery life for

Supplied Accessories

Tripod socket 1/4 (ISO 1222)

Approx. 109.5 x 67.0 x 38.0 mm (4.4 x 2.7 x 1.5 in.) (excluding projections) Dimensions (WxHxD)

Approx. 177 g (6.3 oz) (including battery and memory card) -10° C to $+40^{\circ}$ C (14° F to 104° F) (for land use) 0° C to 40° C (32° F to 104° F) (for underwater use) Weight

Temperature

85% or less (no condensation) Humidity

Strap (Do not swing the camera by the strap. The camera could strike objects or people causing injury and damage to the camera.), EN-EL19 Rechargeable Li-ion Battery, EH-73P Charging AC Adapter (A plug adapter is attached depending on the country or region of purchase. The shape of the plug adapter varies with the country or region of purchase. The EH-73PCH Charging AC Adapter may be included instead of the EH-73P, depending on the country or region where you purchased the camera.), UC-E21 USB Cable, Brush (The brush is used for cleaning the waterproof packing.)

1. All measurements are performed in conformity with Camera and Imaging Products Association (CIPA) standards or guidelines. *1 Dropped from a height of 180 cm (5 ft 10 in.) onto a surface of 5 cm (2 in.) thick plywood (changes in appearance, such as paint peeling off and deformation of the drop shock portion and waterproof performance are not subject to the test). These tests do not guarantee that the camera will be free from damage or trouble under all conditions. *2 Battery life does not reflect the use of SnapBridge and may vary with the conditions of use, including temperature, the interval between shots, and the length of time that menus and images are displayed. *3 Individual movie files cannot exceed 29 minutes in length, even when there is sufficient free space on the memory card for longer recording. The maximum size of a single movie file is 4 GB. If a file exceeds 4 GB even when you record for less than 29 minutes, recording ends.